73012 SHEET 1 OF 1 ISOMETRIC ACTUAL SIZE Ø4.3mm [Ø0.17in] (countersunk) \*ENTTEC recommends the use of M4 countersunk screws 57mm 49mm [2.24in] [1.93in] вне 888 41.5mm 2.5mm [1.63in] [0.1in] 77.2mm 57mm 22.09mm [3.04in] [2.24in] [0.87in]

								FINISH
								(UNLE
1	BASIC DIMENSIONS FLAT DIFFUSER	ROC	29-09-20					
ISSUE	REVISION	DCN / INITIAL	DATE	ISSUE	REVISION	DCN / INITIAL	DATE	

		١.
		Г
	TOLERANCES	С
	(UNLESS OTHERWISE SPECIFIED)	Н
	0.1 UP TO 6mm IS ±0.05	
-	OVER 6 UP TO 30mm IS ±0.10	
	OVER 30MM UP TO 120mm IS ±0.25	h
	OVER 120MM TO 400mm IS ±0.50	ľ
	OVER 400mm IS ±1.00	
	ANGULAR IS ±1/2°	

	DRAWN	ROC	29-09-2	
	CHECKED	JW	29-09-2	
	SCALE	1:1		
	TITLE			

INITIAL

DATE

THIS DOCUMENT AND THE DESIGN IT
CONTAINS IS EXCLUSIVELY THE
PROPERTY OF ENTTEC AND IS THE
SUBJECT OF COPYRIGHT
DRAWN TO AS1100
ALL DIMENSIONS
IN MILLIMETERS

DO NOT SCALE - IF IN DOUBT ASK

ENTTEC enttec.com

73012 - PXL40 SMART PIXEL DOT BASIC DIMENSIONS A3